

## GROUND\_CONT

## GROUND CONTINUITY TESTER



### DESCRIPTION

19 "bay rackmount module for high current earth continuity measurement.  
From the current setpoint programmed between 0 and 30A, it returns the resistance measurement in Ohm.  
Designed for measurement in industrial environments and high speed.  
The GROUND\_CONT module is controlled by an RS422 link.



### FEATURES

#### CONFIGURATION

- RS422 link : transmission speed 19200Bauds  
7 data bits, 1 stop bit, parity even

#### OUTPUT 1 - current

- Max. DC current : 30Adc; Max. Voltage : 12Vdc

#### POWER SUPPLY

- 110 to 230VAC / 50Hz

#### ACCURACY

- Resistance measurement :  
0.1% Full scale +-1 digit  
0.2% FS with mechanical part

#### TEMPERATURE OF CALIBRATION

- 20 to 25°C

#### CASING

- Aluminium case 19" rackable 3U

PRICE	On quote only
WEB LINK	<a href="#">Click here</a>
SECTOR	COIL WINDING
USAGE	COIL WINDING PRODUCTION
WEIGHT	6 Kg
LENGTH	480 mm
WIDTH	380 mm
HEIGHT	133 mm
CUSTOMS CODE	9030390091
C. OF ORIGIN	France
GUARANTEE	1 year
CERTIFICATION	CE
CONTACT	<a href="mailto:commercial@serem-electronics.com">commercial@serem-electronics.com</a>